




Diagramma di portata - Load diagrams - Curvas de cargas - Lastkurven - Courbes de charges - Грузоподъёмные характеристики

RTL 325 B - 20 NORMAL

	(t)	m	15	20	25	30	35	40	45	50	55	60	65
	10	27,93	10,00	10,00	10,00	9,12	7,41	6,14	5,14	4,35	3,70	3,16	2,70
	10	34,47	10,00	10,00	10,00	10,00	9,79	8,05	6,70	5,62	4,74	4,00	
	15	25,13	15,00	15,00	15,00	11,90	9,61	7,90	6,57	5,50	4,63	3,90	
	10	36,28	10,00	10,00	10,00	10,00	10,00	8,69	7,27	6,13	5,20		
	15	25,92	15,00	15,00	15,00	12,40	10,04	8,28	6,90	5,80	4,90	*	
	18	22,40	18,00	18,00	15,70	12,40	10,04	8,28	6,90	5,80	4,90		
	10	37,59	10,00	10,00	10,00	10,00	10,00	9,15	7,68	6,50			
	15	26,96	15,00	15,00	15,00	13,07	10,61	8,78	7,34	6,20	*		
	20	21,37	20,00	20,00	16,50	13,07	10,61	8,78	7,34	6,20			
	10	38,62	10,00	10,00	10,00	10,00	10,00	9,51	8,00				
	15	27,80	15,00	15,00	15,00	13,60	11,07	9,18	7,70	*			
	20	22,03	20,00	20,00	17,14	13,60	11,07	9,18	7,70				
	10	38,87	10,00	10,00	10,00	10,00	10,00	9,60					
	15	28,06	15,00	15,00	15,00	13,77	11,21	9,30	*				
	20	22,24	20,00	20,00	17,34	13,77	11,21	9,30					
	10	35,00	10,00	10,00	10,00	10,00	10,00	10,00					
	15	28,11	15,00	15,00	15,00	13,75	11,10	11,10	*				
	20	22,44	20,00	20,00	17,46	13,75	11,10	11,10					
	10	30,00	10,00	10,00	10,00	10,00	10,00	10,00					
	15	27,90	15,00	15,00	15,00	13,50	13,50	13,50	*				
	20	22,61	20,00	20,00	17,48	13,50	13,50	13,50					

Diagramma di portata - Load diagrams - Curvas de cargas - Lastkurven - Courbes de charges - Грузоподъёмные характеристики

RTL 325 B-20 M-LIFT

	(t)	m	15	20	25	30	35	40	45	50	55	60	65
	10	29,30	10,00	10,00	10,00	9,70	7,92	6,58	5,53	4,70	4,02	3,45	2,97
	10	36,17	10,00	10,00	10,00	10,00	10,00	8,65	7,23	6,10	5,17	4,40	
	15	26,36	15,00	15,00	15,00	12,68	10,28	8,49	7,09	5,97	5,05	4,29	
	10	38,30	10,00	10,00	10,00	10,00	10,00	9,40	7,90	6,70	5,72		
	15	27,33	15,00	15,00	15,00	13,30	10,81	8,95	7,50	6,34	5,39		*
	18	23,62	18,00	18,00	16,78	13,30	10,81	8,95	7,50	6,34	5,39		
	10	39,89	10,00	10,00	10,00	10,00	10,00	9,96	8,40	7,15			
	15	28,59	15,00	15,00	15,00	14,10	11,50	9,55	8,03	6,82			*
	20	22,66	20,00	20,00	17,74	14,10	11,50	9,55	8,03	6,82			
	10	41,17	10,00	10,00	10,00	10,00	10,00	10,00	8,80				
	15	29,62	15,00	15,00	15,00	14,76	12,06	10,04	8,47				*
	20	23,47	20,00	20,00	18,53	14,76	12,06	10,04	8,47				
	10	40,00	10,00	10,00	10,00	10,00	10,00	10,00	10,00				
	15	30,01	15,00	15,00	15,00	15,00	12,28	10,23					*
	20	23,78	20,00	20,00	18,83	15,01	12,28	10,23					
	10	35,00	10,00	10,00	10,00	10,00	10,00	10,00					
	15	30,07	15,00	15,00	15,00	15,00	15,00	12,21					*
	20	24,01	20,00	20,00	19,01	15,05	12,21						
	10	30,00	10,00	10,00	10,00	10,00	10,00						
	15	29,79	15,00	15,00	15,00	15,00							*
	20	24,15	20,00	20,00	19,10								


(*) + 200 kg

utilizzando bozzello singolo - using single hoist block - usando un solo bloque - verwenden eines einzelnen Block - utilisation d'un seul moufle - с помощью одного блока

Altezza torre - Tower height - Altura torre - Turmhohe - Hauteur de la tour - ИСПОЛНЕНИЯ БАШНИ

HR23


RT1	SERVICE	OUT OF SERVICE
R1	- 2240 kN	- 4120 kN
R2	1620 kN	3570 kN
V	1260 kN	



RT1

MAX H (m)		
	FEM 1001	C 25
30	60.40	54.40
35	54.40	54.40
40	54.40	48.40
45	54.40	48.40
50	48.40	48.40
55	48.40	42.40
60	48.40	42.40
65	42.40	42.40


RT2	SERVICE	OUT OF SERVICE
R1	- 2640 kN	- 4930 kN
R2	1940 kN	4330 kN
V	1390 kN	



RT2

MAX H (m)		
	FEM 1001	C 25
30	72.40	66.40
35	66.40	60.40
40	66.40	60.40
45	66.40	60.40
50	60.40	54.40
55	60.40	54.40
60	54.40	54.40
65	54.40	48.40

RTB	SERVICE	OUT OF SERVICE
R1	- 3090 kN	- 6800 kN
R2	2320 kN	6130 kN
V	1540 kN	



RTB

MAX H (m)		
	FEM 1001	C 25
30	78.40	72.40
35	78.40	72.40
40	78.40	72.40
45	72.40	66.40
50	72.40	66.40
55	66.40	60.40
60	66.40	60.40
65	66.40	60.40

Altezze diverse e combinazioni di torre sono disponibili; consultateci - Different height and tower combinations are available; please consult us

Hay diferentes alturas y combinaciones de torre disponibles. Consúltenos - Andere Höhen und Turmkombinationen auf Anfrage

Différentes hauteurs et combinaisons de tour sont disponibles; nous consulter


Возможны другие сочетания высоты и конфигурации башни; проконсультируйтесь с нами

Altezza torre - Tower height - Altura torre - Turmhohe - Hauteur de la tour - ИСПОЛНЕНИЯ БАШНИ

HP20


RTB1 RAP1	SERVICE	OUT OF SERVICE
R1	- 2860 kN	- 3240 kN
R2	2200 kN	2710 kN
V	1320 kN	

RTB RAP	SERVICE	OUT OF SERVICE
R1	- 3020 kN	- 3920 kN
R2	2330 kN	3380 kN
V	1370 kN	



**RTB1
RAP1**

MAX H (m)		
	FEM 1001	C 25
30	47.90	44.15
35	44.15	40.40
40	44.15	40.40
45	40.40	36.65
50	40.40	36.65
55	36.65	32.90
60	36.65	32.90
65	32.90	29.15



**RTB
RAP**

MAX H (m)		
	FEM 1001	C 25
30	53.15	53.15
35	49.40	49.40
40	49.40	49.40
45	45.65	45.65
50	45.65	45.65
55	41.90	41.90
60	41.90	41.90
65	38.15	38.15

Altezze diverse e combinazioni di torre sono disponibili; consultateci - Different height and tower combinations are available; please consult us

Hay diferentes alturas y combinaciones de torre disponibles. Consúltenos - Andere Höhen und Turmkombinationen auf Anfrage

Différentes hauteurs et combinaisons de tour sont disponibles; nous consulter


Возможны другие сочетания высоты и конфигурации башни; проконсультируйтесь с нами

Zavorramento - Counterweight - Bloque de contrapeso - Gegengewichtsblöcke - Bloc de contrepoid - Плиты противовеса


	65m			60m			55m			50m			45m			40m			35m			30m		
	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
	1	5	0	1	5	0	1	5	0	1	5	0	1	5	0	1	5	0	1	4	1	1	4	1
	30000 kg			30000 kg			30000 kg			30000 kg			30000 kg			30000 kg			27000 kg			27000 kg		

Altre Installazioni - Other configurations - Otras Implantaciones - Aufstellmöglichkeiten - Autres Im-plantations -
Другие варианты компоновки башни

INTERNAL CLIMBING



EXTERNAL CLIMBING



C25 - H<120m


HR23 22.6			
	A min/max (m)	B min/max (m)	C max (m)
30m	28/40	24/36	44
35m	28/40	22/34	42
40m	22/34	20/32	40
45m	22/34	20/30	38
50m	22/34	20/26	34
55m	22/28	18/24	32
60m	22/28	16/22	30
65m	22/28	14/20	28


HP20		
	H (m)	C (m)
①		

HP20			
	A min/max (m)	B min/max (m)	C max (m)
①			

① Altezze diverse e combinazioni di torre sono disponibili; consultateci - Different height and tower combinations are available; please consult us
Hay diferentes alturas y combinaciones de torre disponibles. Consúltenos - Andere Höhen und Turmkombinationen auf Anfrage
Différentes hauteurs et combinaisons de tour sont disponibles; nous consulter
Возможны другие сочетания высоты и конфигурации башни; проконсультируйтесь с нами

Meccanismi - Mechanisms- Mecanismos - Antriebe - Mécanismes - Приводы



80 HVF 100		t	m/min	
 80 kW		10	0	→ 38
		6	0	→ 60
		3	0	→ 100
		1.1	0	→ 210
		15	0	→ 25
		11.2	0	→ 33
		8	0	→ 44
		1.65	0	→ 140
 max 970 m		20	0	→ 19
		12	0	→ 30
		5.6	0	→ 57
		2.2	0	→ 105

	67	kW	15° → 85°	1.8	min
	2 x 11	kW	0 →	0.8	rpm

 2000/14/CEE 2005/88/CEE	 2006/95/CEE	400 V	50 Hz	I _{max} =	320	A	Fuse=	350	A	MACHINE RATING	MAX GENERATOR
		460 V	60Hz	I _{max} =	278	A	Fuse=	300	A	212 kVA	339 kVA

(*)  65 m - 80HVF100







X7




X8






(*) Parte rotante - Slewing crane part - Parte rotativa - Drehender Kranteil - Partie tournante - Поворотная часть			Lunghezza Lenght Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Quantità Quantity Cantidad Menge Quantité Количество	Peso Weight Peso Gewicht Poids вес
Tronco braccio Jib section Elemento de flecha Auslegerement Elément de flèche Секция стрелы	1		10,56 m	1,84 m	2,00 m	1	2380 kg
	2		10,52 m	1,79 m	1,79 m	1	1345 kg
	3		10,52 m	1,79 m	1,79 m	2	1155 kg
	4		5,35 m	1,79 m	1,79 m	1	586 kg
	5		10,61 m	1,80 m	1,90 m	1	1525 kg
	6		10,52 m	1,79 m	1,79 m	1	1155 kg

Ingombri e pesi - Dimensions and weight - Dimensões e pesos - Abmessungen und Gewicht - Encombrent et poids - Габариты, размеры и вес

Torre - Tower - Torre - Turm - Tour - Башня		Lunghezza Lenght Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Peso Weight Peso Gewicht Poids вес
HR23 22.6		6,00 m	2,28 m	2,29 m	4815 kg
HR23 26.6		6,00 m	2,32 m	2,34 m	6266 kg
HR23 TB12		12,00 m	2,36 m	2,39 m	14986 kg
HP20 3.75		3,75 m	1,95 m	2,10 m	2972 kg
HP20 TB10		10,00 m	1,95 m	2,10 m	7000 kg
HP20 TB11.5		11,50 m	1,95 m	2,10 m	9360 kg

Accessori - Accessories - Accesorios - Zubehör - Accessoires - аксессуары		Lunghezza Lenght Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Peso Weight Peso Gewicht Poids вес
Gabbia di telescopaggio - Telescoping cage - Teleskopkäfig - Cage télescopique HR23		11,98 m	4,14 m	4,16 m	22730 kg

Ingombri e pesi - Dimensions and weight - Dimensões e pesos - Abmessungen und Gewicht - Encombrent et poids - Габариты, размеры и вес

Ancoraggi - Anchors - Anclajes - Verankerungen - Anchorages - Анкера		Lunghezza Lenght Longitud Länge Longueur длина	Larghezza Width Anchura Breite Largeur ширина	Altezza Height Altura Höhe Hauteur высота	Peso Weight Peso Gewicht Poids вес
HR23-22 RT1		2,02 m	0,80 m	0,80 m	490 kg
HR23-26 RT2		2,62 m	0,80 m	0,80 m	830 kg
HR23-30 RTB		2,62 m	0,80 m	0,80 m	1030 kg
HP20 RTB		1,74 m	0,70 m	0,70 m	565 kg
HP20 RTB1		1,92 m	0,60 m	0,60 m	420 kg
HP20 RAP		0,44 m	0,72 m	0,72 m	470 kg
HP20 RAP1		0,69 m	0,65 m	0,65 m	270 kg

MORITSCH CRANES S.R.L.

Via Ramentera, 52
32035 Santa Giustina - BL - Italy
+39 0437 1840396 - info@moritsch.it
www.moritsch.it